



LOCK WASHER NSK-EL

Secures electrical slotted screw connections effectively and permanently

Item	Material	Ø ID	Ø OD	S	H
NSK EL6	C60, 1.1221*	6.10 + 0.48	Ø 14.20-0.43	1.80±0.05	2.00+0.20
NSK EL8	C60, 1.1221*	8.20 + 0.58	Ø 18.20-0.43	2.00±0.05	2.20+0.30
NSK EL10	C60, 1.1221*	10.20 + 0.58	Ø 22.25-0.52	2.20±0.10	2.40+0.35
NSK EL12	C60, 1.1221*	12.30 + 0.58	Ø 27.25-0.52	2.40±0.10	2.60+0.35
NSK EL6	1.4401 / A4	6.10 + 0.48	Ø 14.20-0.43	2.20±0.05	2.20+0.20
NSK EL8	1.4401 / A4	8.20 + 0.58	Ø 18.20-0.43	2.20±0.05	2.40+0.30
NSK EL10	1.4401 / A4	10.20 + 0.58	Ø 22.25-0.52	2.40±0.10	2.60+0.35
NSK EL12	1.4401 / A4	12.30 + 0.58	Ø 27.25-0.52	2.60±0.10	2.80+0.35

*GEOMET plated