



LOCK WASHER NSK-K

Toothed version for electrically joints through painted surfaces

Item	Material	Ø ID	Ø OD	S	H
NSK-K 4	C60, 1.1221*	4,10 +0,48	8,20 -0,40	1,00 ±0,03	1,30 ±0,20
NSK-K 5	C60, 1.1221*	5,10 +0,48	10,20 -0,40	1,00 ±0,03	1,50 ±0,20
NSK-K 6	C60, 1.1221*	6,10 +0,48	12,20 -0,40	1,20 ±0,04	1,90 ±0,20
NSK-K 8	C60, 1.1221*	8,20 +0,58	16,20 -0,50	1,40 ±0,04	2,40 ±0,25
NSK-K 10	C60, 1.1221*	10,20 +0,58	20,25 -0,50	1,60 ±0,04	2,75 ±0,25
NSK-K 12	C60, 1.1221*	12,40 +0,58	24,25 -0,50	1,60 ±0,04	3,00 ±0,25
NSK-K 4	1.4401 / A4	4,10 +0,48	8,20 -0,40	1,00 ±0,03	1,30 ±0,20
NSK-K 5	1.4401 / A4	5,10 +0,48	10,20 -0,40	1,00 ±0,03	1,50 ±0,20
NSK-K 6	1.4401 / A4	6,10 +0,48	12,20 -0,40	1,20 ±0,04	1,90 ±0,20
NSK-K 8	1.4401 / A4	8,20 +0,58	16,20 -0,50	1,40 ±0,04	2,40 ±0,25
NSK-K 10	1.4401 / A4	10,20 +0,58	20,25 -0,50	1,60 ±0,04	2,75 ±0,25
NSK-K 12	1.4401 / A4	12,40 +0,58	24,25 -0,50	1,60 ±0,04	3,00 ±0,25