



LOCK WASHER NSK-L

for slotted hole fastenings with limited installation space

Item	Material	Ø ID	Ø OD	S	H
NSK-L 6	C60, 1.1221*	6,10 +0,48	14,20 -0,43	2,40 ±0,04	3,10 ±0,20
NSK-L 8	C60, 1.1221*	8,20 +0,58	18,20 -0,52	2,40 ±0,05	3,40 ±0,25
NSK-L 10	C60, 1.1221*	10,20 +0,58	22,25 -0,52	2,80 ±0,06	3,70 ±0,25
NSK-L 12	C60, 1.1221*	12,40 +0,58	27,25 -0,52	2,80 ±0,06	4,30 ±0,25
NSK-L 14	C60, 1.1221*	14,40 +0,58	30,25 -0,52	3,50 ±0,06	4,70 ±0,25
NSK-L 16	C60, 1.1221*	16,40 +0,58	32,50 -0,52	3,50 ±0,07	4,90 ±0,30
NSK-L 20	51CrV4, 1.8159*	21,00 +0,58	40,00 -0,52	4,00 ±0,07	6,00 ±0,30
NSK-L 6	1.4401 / A4	6,10 +0,48	14,20 -0,43	2,40 ±0,04	3,10 ±0,20
NSK-L 8	1.4401 / A4	8,20 +0,58	18,20 -0,52	2,40 ±0,05	3,40 ±0,25
NSK-L 10	1.4401 / A4	10,20 +0,58	22,25 -0,52	2,80 ±0,06	3,70 ±0,25
NSK-L 12	1.4401 / A4	12,40 +0,58	27,25 -0,52	2,80 ±0,06	4,30 ±0,25
NSK-L 14	1.4401 / A4	14,40 +0,58	30,25 -0,52	3,50 ±0,06	4,70 ±0,25
NSK-L 16	1.4401 / A4	16,40 +0,58	32,50 -0,52	3,50 ±0,07	4,90 ±0,30
NSK-L 20	1.4401 / A4	21,00 +0,58	40,00 -0,52	4,00 ±0,07	6,00 ±0,30

*GEOMET plated