



SPERRKANTSCHREIBEN NSK-EL

Sichert elektrische Langlochschaubenverbindungen effektiv und dauerhaft

Variante Federstahl GEOMET beschichtet

NSK E	Für Gewinde M	DI	DA	S	H
NSK EL6	6	6.10 + 0.48	∅ 14.20-0.43	1.80±0.05	2.00+0.20
NSK EL8	8	8.20 + 0.58	∅ 18.20-0.43	2.00±0.05	2.20+0.30
NSK EL10	10	10.20 + 0.58	∅ 22.25-0.52	2.20±0.10	2.40+0.35
NSK EL12	12	12.30 + 0.58	∅ 27.25-0.52	2.40±0.10	2.60+0.35

Variante Edelstahl A4 (1.4401)

NSK E	Für Gewinde M	DI	DA	S	H
NSK EL6	6	6.10 + 0.48	∅ 14.20-0.43	2.20±0.05	2.20+0.20
NSK EL8	8	8.20 + 0.58	∅ 18.20-0.43	2.20±0.05	2.40+0.30
NSK EL10	10	10.20 + 0.58	∅ 22.25-0.52	2.40±0.10	2.60+0.35
NSK EL12	12	12.30 + 0.58	∅ 27.25-0.52	2.60±0.10	2.80+0.35