



SPRING LOCK WASHER NSK-E

Version spring steel GEOMET plated				
NSK E	For metrical Thread M	DA	S	H
NSK E3	3	Ø 7.10-0.30	1.00±0.05	1.10+0.20
NSK E4	4	Ø 9.10-0.40	1.20±0.05	1.30+0.20
NSK E5	5	Ø 9.10-0.40	1.20±0.05	1.50+0.20
NSK E6	6	Ø 12.10-0.43	1.60±0.05	1.70+0.20
NSK E8	8	Ø 16.10-0.43	1.60±0.05	2.20+0.25
NSK E10	10	Ø 20.10-0.52	1.80±0.10	2.30+0.35
NSK E12	12	Ø 24.10-0.52	2.00±0.10	2.50+0.35
NSK E16	16	Ø 30.10-0.52	2.20±0.10	2.70+0.35
<i>We reserve the right to make technical changes as product development has not yet been completed.</i>				
Version stainless steel A4 (1.4401)				
NSK E	For metrical Thread M	DA	S	H
NSK E3	3	Ø 7.30-0.40	1.00±0.05	1.10+0.20
NSK E4	4	Ø 9.40-0.40	1.2±0.05	1.90+0.20
NSK E5	5	Ø 10.10-0.40	1.2±0.05	2.00+0.20
NSK E6	6	Ø 12.10-0.43	2.25±0.075	2.20+0.20
NSK E8	8	Ø 16.10-0.43	2.25±0.075	2.80+0.25
NSK E10	10	Ø 20.10-0.52	2.4±0.10	3.00+0.35
NSK E12	12	Ø 24.10-0.52	2.7±0.10	3.40+0.35
NSK E16	16	Ø 30.10-0.52	3.0±0.10	3.60+0.35
<i>We reserve the right to make technical changes as product development has not yet been completed.</i>				